



Bhagat Phool Singh Mahila Vishwavidyalaya
Department of Engineering Cell
Khanpur Kalan (Sonapat), Haryana-131305

Office No. 01263-283007,283530, Fax No. 01263-283779, www.bpswomenuniversity.ac.in

NOTICE INVITING TENDER

Sealed tenders as per schedule/DNIT attached are hereby invited on behalf of Registrar in her Office at BPSMV Khanpur Kalan through Registered post/speed post Eligible Contractors enlisted with Haryana PWD (B&R)/CPWD/MES and Labour & Construction Co-operative Societies for the below noted work. If the date on which the tenders are to be received is declared holiday then the tender will be received on the next working day. The tender shall be opened on the same day in the presence of the tenderer or the authorized representative/agents who may like to be present at that time:-

Sr. No.	Name of Work	App. Cost.	Time Limit	Date & Time for Receiving of Tender		Date & Time for opening of Tender	
				Date	Time	Date	Time
1.	Tender for Special Repair work of 1882 sft. House no. 5 at B.P.S.M.V. Khanpur Kalan .	1,64,700/-	20 days	07.10.2022	1:00 pm	07.10.2022	3:00 pm

- 1 The rates of all items should be quoted on item rate basis.
- 2 The limited tenders/quotations may be sent in favour of Registrar, BPSMV Khanpur Kalan, in sealed envelope through Registered Post/Speed Post with mentioning tender name in bold letter on the envelop.
- 3 Engineering –In-Charge is competent to increase/decrease the quantity of work.
- 4 Central/ State taxes will be deducted from the work done amount as applicable from time to time.
- 5 The work shall be executed as per specifications given in the DNIT.

SDE (Civil)
For Registrar

Endst. No./ BPSMV /Engg./22/

Dated

A copy of the above is forwarded to the following for information and necessary action:-

1. Notice Board.

SDE (Civil)

DETAILED NOMINCLATURE.

NAME OF WORK:- Tender for Special Repair work of 1882 sft. House no. 5 at B.P.S.M.V. Khanpur Kalan

Approx. Cost : 1,64,700/-

Date of Tender: 07.10.2022

Sr. No.	Description of items	Qty.	Unit	Rate to be quoted by the agency in words and in figures, FOR including VAT & taxes.	
				In Figure	In Word
1.	Distemping with 1st quality acrylic distemper, having voe (Volatile Organic Compound) content less than 50 grams/ litre, of approved brand and manufacture, including applying additional coats wherever required, to achieve even shade and colour. HSR:-11.66.2 Two coats	771.45	Sqm.		
2.	Finishing walls with Acrylic Smooth exterior paint of required shade: Old work (Two or more coat applied @ 1.67 litre/ 10 sqm) on existing cement paint surface (HSR-30.37.1)	638.79	Sqm.		
3.	Providing and applying two coats white cement based putty of approved brand and manufacturer, over plastered surface and grinding the surface smooth with sand paper to get an even and smooth finish including cost and carriage of all material , labour charges, scaffolding, sundries etc. complete. HSR:-11.58	211.54	Sqm.		
4.	Painting two coats excluding priming coat with synthetic enamel paint in all shades on new wood work or metallic or plastered or concrete surfaces to give an even shade. HSR:-11.78.	292.67	Sqm.		
5.	Dismantling old plaster or skirting raking out joints and cleaning the surface for plaster including disposal of rubbish to the dumping ground within 50 metres lead. HSR:-5.45 + 15 mm cement plaster on the rough side of single or half brick wall of mix : 1 :4 (1 cement: 4 fine sand). HSR:- 11.6.1 .	50	Sqm.		
6.	Providing and fixing ISi marked flush door shutters conforming to IS : 2202 (Part I) decorative type, core of block board construction with frame of 1st class hard wood and well matched teak 3 ply veneering with vertical grains or cross bands and face veneers on both faces of shutters. HSR:-12.36.1 35 mm thick including ISi marked Stainless Steel butt hinges with sqm necessary screws	1.83	Sqm.		
7.	Providing and fixing wire gauge shutters using galvanized M.S. wire gauge of average width of aperture 1.4 mm in both directions with wire of dia 0.63 mm, for doors, windows and lerestory windows with hinges and necessary screws: 35 mm thick shutters HSR :- 12.19.1.2.2 Kiln seasoned and chemically treated Hollock wood.	1.88	Sqm.		

8.	Providing and fixing glazed shutters for doors, windows and clerestory windows using 4 mm thick float glass panes, including ISI marked M.S. pressed butt hinges bright finished of required size with necessary screws. Kiln seasoned and chemically treated Hollock wood HSR:-12.10.2.1 35 mm thick	2.52	Sqm.		
9.	Providing and fixing panelling or panelling and glazing in panelled or panelled and glazed shutters for doors, windows and clerestory windows (Area of opening for panel inserts excluding portion inside grooves or rebates to be measured). Panelling for panelled or panelled and glazed shutters 25 mm to 40 mm thick: HSR:- 12.9.8 Fly proof stainless steel grade 304 wire gauge with 0.5 mm dia. wire and 1.4mm wide aperture with matching wood beading.	5.02	Sqm.		
10.	Providing and fixing panelling or panelling and glazing in panelled or panelled and glazed shutters for doors, windows and clerestory windows (Area of opening for panel inserts excluding portion inside grooves or rebates to be measured). Panelling for panelled or panelled and glazed shutters 25 mm to 40 mm thick: HSR:- 12.9.7.1 Float glass panes 4 mm thick glass pane (weight not less than sqm 10kg/sqm).	2.81	Sqm.		
11	Providing and fixing Pre-laminated flat pressed 3 layer (medium density) particle board or graded wood particle board IS : 3087 marked, with one side decorative and other side balancing lamination Grade I, Type II exterior grade IS : 12823 marked, in shelves with screws and fittings wherever required, edges to be painted with polyurethane primer (fittings to be paid separately) . HSR:-12.27.1 18 mm thick	5.95	Sqm.		
12	Providing and placing on terrace water storage tank, IS: 12701 Make- Sintex, Supreme or equivalent, with cover and suitable locking arrangement and making necessary holes for inlet, outlet and overflow pipes but without fittings and the base support for tank having. (HSR-22.181)	2500	Ltr.		
13	Providing and fixing ball valve (brass) of approved quality, High or low pressure, with plastic floats complete : 25 mm nominal bore (HSR-22.103.3)	1	Each		
14	Providing and fixing gun metal gate valve with C.I. wheel of approved quality (screwed end):20 mm nominal bore (HSR-22.98.2)	4	Each		
15	Providing and fixing gun metal gate valve with C.I. wheel of approved quality (screwed end):80 mm nominal bore (HSR-22.98.7)	1	Each		
16	Providing and fixing C.P. Brass extension nipple(size 15mmx50mm) of approved make and quality as per direction of Engineer-in-charge. (HSR-22.109)	3	Each		
17	Providing and fixing C.P. brass stop cock (concealed) of standard design and of approved make conforming to IS:8931. 15 mm nominal bore (HSR-22.107.1)	3	Each		
18	Providing and fixing 8 mm dia C.P. I S.S. Jet with flexible tube up to 1 metre long with S.S. triangular plate to European type W.C. of quality and make as approved by Engineer - in - charge. (HSR-22.38)	4	Each		
19	Providing and fixing P.V.C. low level flushing cistern with manually controlled device (handle lever) conforming to IS : 7231, with all fittings and fixtures	1	Each		

	complete. 1 o litre capacity - White (22.39)				
20.	Providing and fixing wash basin with C.I. brackets, 15 mm C.P. brass pillar taps, 32 mm C.P. brass waste of standard pattern, including painting of fittings and brackets, cutting and making good the walls wherever require: White vitreous chinaware Wash basin size 630x450 mm with 2270 pair of 15 mm C. P. brass pillar taps (HSR-22.1.1)	1	Each		
21	Providing and fixing P.V.C. waste pipe for sink or wash basin including P.V.C. waste fittings complete. Flexible pipe 40mm dia (HSR-22.14.2.2)	6	Each		
22	Providing and fixing G.I. Union in G.I. pipe including cutting and threading the pipe and making long screws etc. complete (New work) : 20 mm nominal bore (HSR-22.94.2)	9	Each		
23	Providing and fixing Un plasticised PVC connection pipe with brass unions: 15 mm nominal bore (HSR-22.101.2.1)	4	Each		
24	Providing and fixing C.P. brass long body bib cock of approved quality conforming to IS standards and weighing not less than 690 gms. (HSR-22.106.1) 15 mm nominal bore	6	Each		

JE (Civil)

SDE (Civil)