



Bhagat Phool Singh Mahila Vishwavidyalaya
Department of Engineering Cell
Khanpur Kalan (Sonapat), Haryana-131305

Office No. 01263-283007,283530, Fax No. 01263-283779, www.bpswomenuniversity.ac.in

NOTICE Re-INVITING TENDER

Sealed tenders as per schedule/DNIT attached are hereby Re-invited on behalf of Registrar in her Office at BPSMV Khanpur Kalan through Registered post/speed post Eligible Contractors enlisted with Haryana PWD (B&R)/CPWD/MES and Labour & Construction Co-operative Societies for the below noted work. If the date on which the tenders are to be received is declared holiday then the tender will be received on the next working day. The tender shall be opened on the same day in the presence of the tenderer or the authorized representative/agents who may like to be present at that time:-

Sr. No.	Name of Work	App. Cost.	Time Limit	Date & Time for Receiving of Tender		Date & Time for opening of Tender	
				Date	Time	Date	Time
1.	Tender for Special Repair work of 1882 sft. House no. 15 at B.P.S.M.V. Khanpur Kalan . Re-Invited (Ind time)	1,03,200/-	15 days	14.10.2022	1:00 pm	14.10.2022	3:00 pm

1. The rates of all items should be quoted on percentage rate basis.
2. The limited tenders/quotations may be sent in favour of Registrar, BPSMV Khanpur Kalan, in sealed envelope through Registered Post/Speed Post with mentioning tender name in bold letter on the envelop.
3. Engineering –In-Charge is competent to increase/decrease the quantity of work.
4. Central/ State taxes will be deducted from the work done amount as applicable from time to time.
5. The work shall be executed as per specifications given in the DNIT.

SDE (Civil)
For Registrar

Endst. No./ BPSMV /Engg./22/

Dated

A copy of the above is forwarded to the following for information and necessary action:-

1. Notice Board.

SDE (Civil)

DETAILED NOMINCLATURE.

NAME OF WORK:- Tender for Special Repair work of 1882 sft. House no. 15 at B.P.S.M.V. Khanpur Kalan

Approx. Cost : 1,03,200/-

Date of Tender: 14.10.2022

Sr. No.	Description of items	Qty.	Unit	Rate to be quoted by the agency in words and in figures, FOR including VAT & taxes.	
				In Figure	In Word
1.	Distemping with 1st quality acrylic distemper, having voe (Volatile Organic Compound) content less than 50 grams/ litre, of approved brand and manufacture, including applying additional coats wherever required, to achieve even shade and colour. HSR:-11.66.2 Two coats	771.45	Sqm.		
2.	Providing and applying two coats white cement based putty of approved brand and manufacturer, over plastered surface and grinding the surface smooth with sand paper to get an even and smooth finish including cost and carriage of all material , labour charges, scaffolding, sundries etc. complete. HSR:-11.58	282.05	Sqm.		
3.	Painting two coats excluding priming coat with synthetic enamel paint in all shades on new wood work or metallic or plastered or concrete surfaces to give an even shade. HSR:-11.78.	292.67	Sqm.		
4.	12 mm thick cement plaster in 1:6 cement sand mortar. HSR:-11.5.4	100	Sqm.		
5.	Treatment of soil under existing floors using chemical emulsion @ one litre per hole, 300 mm apart including drilling 12 mm diameter holes and plugging with cement mortar 1 :2 (1 cement : 2 Coarse sand) to match the existing floor: With Chlorpyriphos/Lindane E.C. 20% sqm with 1 % concentration (HSR-4.40.3.1)	174.84	Sqm.		
6	Providing and fixing Pre-laminated flat pressed 3 layer (medium density) particle board or graded wood particle board IS : 3087 marked, with one side decorative and other side balancing lamination Grade I, Type II exterior grade IS : 12823 marked, in shelves with screws and fittings wherever required, edges to be painted with polyurethane primer (fittings to be paid separately) . HSR:-12.27.1 18 mm thick	8.92	Sqm		
7	Providing and fixing wire gauge shutters using galvanized M.S. wire gauge of average width of aperture 1.4 mm in both directions with wire of dia 0.63 mm, for doors, windows and clerestory windows with hinges and necessary screws: 35 mm thick shutters HSR :-12.19.1.2.2 Kiln seasoned and chemically treated Hollock wood.	3.82	Sqm.		

8	Providing and fixing ISi marked flush door shutters conforming to IS : 2202 (Part I) non-decorative type, core of block board construction with frame of 1st class hard wood and well matched commercial 3 ply veneering with vertical grains or cross bands and face veneers on both faces of shutters: HSR:-12.37.1 35 mm thick including ISi marked Stainless Steel butt hinges with necessary screw	1.46	Sqm.		
9.	Providing and fixing panelling or panelling and glazing in panelled or panelled and glazed shutters for doors, windows and clerestory windows (Area of opening for panel inserts excluding portion inside grooves or rebates to be measured). Panelling for panelled or panelled and glazed shutters 25 mm to 40 mm thick: HSR:- 12.9.7.1 Float glass panes 4 mm thick glass pane (weight not less than sqm 10kg/sqm).	2.19	Sqm.		
10.	Providing and fixing 600x450 mm bevelled edge mirror of superior glass (of approved quality) complete with 6 mm thick hard board ground fixed to wooden cleats with C.P. brass screws and washers complete (HSR-22.209)	3	Each		
11.	Providing and fixing panelling or panelling and glazing in panelled or panelled and glazed shutters for doors, windows and clerestory windows (Area of opening for panel inserts excluding portion inside grooves or rebates to be measured). Panelling for panelled or panelled and glazed shutters 25 mm to 40 mm thick: Ply wood 5 ply, 9 mm thick Decorative plywood both side decorative veneer sqm (Type - I) conforming to IS 1328 BWR type (HSR-12.9.3.1)	1.15	Sqm.		

JE (Civil)

SDE (Civil)